

Baumit EasyPrimer

Primer



- **Vapour-permeable primer**
- **For absorbent & chalking surfaces**
- **Low-emission, solvent & softener free**

Product Overview

Vapour-permeable, low-emission, free of solvents and softeners primer coat. For the pre-treatment of absorbent, chalking and porous substrates, such as gypsum construction board, drywall and gypsum fibreboard prior to the application of Baumit KlimaColor.

Use: For internal use to prepare walls prior to the application of Baumit KlimaColor.

Composition

Acrylate dispersion, water, additives, preservative

Properties

- Primer for use on all common internal walls and ceilings
- Reduces the absorbency of porous substrates such as plasterboards, gypsum plasterboards and gypsum fibreboards

Application

Dilute Baumit EasyPrimer with water – up to 2:1 for highly absorbent substrates and up to 1:1 in the case of weakly absorbent substrates.

Apply with a brush or roller.

All sufficient drying time of approx. 6 hours (+20 °C/65 % relative humidity) before applying the subsequent paint layers.

Technical Data

	Baumit EasyPrimer 5 L	Baumit EasyPrimer 10 L
consumption	0.1 l/m ²	0.1 l/m ²
yield	50 m ² /carton	100 m ² /carton

Delivery Format

10 L carton, 1 pallet = 60 canisters = 600 L

Storage

Can be stored for 24 months if unopened in original packaging.

Quality Assurance

Internal quality assurance is provided by the manufacturer's plant.

Classification of Chemicals

Gather the detailed classification from the Safety Data Sheet (according article 31 and annex II of the regulation No. 1907/2006 of the European Parliament and –Council from 18.12.2006) at www.baumit.com or request the Safety Data Sheet at the respective production plant.

Subsurface

Suitable for use on:

- Gypsum construction board
- Gypsum plasterboards
- Drywall
- Gypsum fibreboard

Not suitable for use on plastic, wood or wood-based materials.

**Subsurface
Pre-treatment**

The substrate must be firm, clean, dry and load-bearing, as well as free from mold, sintered layers and separating agents. Plastics, wood and wood-based materials are not suitable. Check existing old coatings for load-bearing capacity. Remove non-stable coatings (e.g. glue paint).

Processing

Dilute Baunit EasyPrimer with water up to 1: 2 for highly absorbent substrates, up to 1: 1 for weakly absorbent substrates and apply by brush or roller. Further paint build-up after sufficient drying time, usually after approx. 6 hours (+20 ° C / 65%rel. Humidity).

Application recommendation:

Outside areas or highly absorbent surfaces - undiluted
Indoor areas or areas with low suction - 1:1 to 1:2

**Notes and General
Informations**

The air, material and substrate temperature must be above +5 °C during processing and the setting. Used tools must be cleaned with soap and water immediately after use.

Disposal: at hazardous waste incineration or hand in at a hazardous waste collection point. Must not be allowed to enter the sewerage system, water bodies or soil. Only completely empty containers should be recycled.

Safety precautions: Keep out of reach of children. Ensure thorough ventilation during processing and drying. Avoid eating, drinking, and smoking during application of the primer. In case of contact with eyes or skin, rinse immediately with plenty of water. Further information can be found in the EU - safety data sheet which is available at the company address.

Written and oral application technology recommendations provided by us to assist the seller/processor are based on our experience and reflect the current state of the art in science and practical application know-how. However, it is understood that these recommendations are non-binding. They do not create any legal relationship or any ancillary obligations in connection with the sale contract. They do not release the buyer from its obligation to verify the suitability to our products for the intended purpose or use by itself.